

PRODUCT INFORMATION

Purging Compounds

Purgex[™] 602 Plus Commercial Purging Compound is a ready-to-use blend consisting of active ingredients with a polystyrene carrier. Purgex[™] products have mechanical activity for efficient cleaning, foaming action for enhanced mixing and a lubricant for easy removal. Purgex[™] thoroughly and safely cleans injection molding machines and hot runner systems. All active ingredients in Purgex[™] are Generally Recognized As Safe (GRAS) by the US FDA.

Physical Description:

- Blend, polystyrene and an FDA-approved active component
- Non-toxic, non-abrasive, and safe
- Ready to use and easy to remove

Process:	☑ Injection Molding	☐ Injection Blow Molding	☐ Extrusion- Blow Molding	☐ Extrusion- Profile
	☐ Extrusion- Compounding	☐ Extrusion- Sheet	☐ Blown Film	
Works Best on These Resins:	☑ PC	☑ PS	☑ SAN	
Amount Needed:	1 to 1.5 times barrel capacity, depending on condition of machine/tool and colorant/ additive loading.			
Temperature Range:	360°F to 550°F (183°C to 288°C)			
Recommended for:	✓ Hot Runners✓ Cold Runners	✓ Mixing Nozzles☐ Extrusion Dies	☑ Check Valves ☐ Melt Pumps	☐ Accumulators

Features & Benefits:

- ✓ Specifically designed for clear resins, Purgex[™] 602 Plus efficiently removes residual contamination from the screw and barrel in injection molding machines and extruders and effectively cleans hot runner systems.
- ✓ Purgex™ 602 Plus performs fast and efficient color and material changes with PC and PS resins and their copolymers.
- ✓ Purgex™ 602 Plus greatly reduces/eliminates the haze that is often left after purging with polyolefin-based purging compounds.
- ✓ The active ingredients in Purgex[™] 602 Plus help prevent degradation of the polystyrene carrier.
- ✓ With regular use, Purgex[™] forms a temporary barrier which protects steel surfaces from oxidation, extending the cleaning process.

Copyright 2013 Neutrex, Inc. All rights reserved - Revision B: 3/20/13